

1600~1790nm 1x5 Fused Fiber Splitter Module

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	1X5
Center Wavelength	nm	1625, 1650, 1700, 1730, 1750, 1790
Passband Width	nm	+/-20
Insertion Loss	dB	≤9.0
PDL	dB	≤0.3
Uniformity	dB	≤1.6
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 4. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLT-	NNNN	-	NXN	- (C)	C	NN	-CC/CCC
	Center Wavelength		Configuration	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	1625=1625nm		1X5= 1x5 Type	V=SM1950 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
	1700=1700nm			O=10/130 DC Fiber	L= Loose Tube	10= 1.0m	FC/APC=FC/APC Connector
	1730=1730nm			Blank for SMF-28 Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	1790=1790nm				3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector