

2000nm 1x5 Fused Fiber Splitter Module for Pulse Power

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	1X5
Center Wavelength	nm	1900, 1950, 2000, 2050
Passband Width	nm	+/-20
Insertion Loss	dB	≤9.0
PDL	dB	≤0.3
Uniformity	dB	≤1.6
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O)
Fiber Tensile Load	N	5
Maximum Average Power	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 25, 30, 40, 50, 60, 80, 100
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLT- NNNN	-	NXN	-H NN	P NN	- (C)	C	NN	- CC/CCC
<i>Center Wavelength</i>		<i>Configuration</i>	<i>Average Power</i>	<i>Peak Power</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>
1900-1900nm		1X5- 1x5 Type	03- 300mW	01- 100W	V-SM1950 Fiber	B- Bare Fiber	05-0.5m	N-Without Connector
1950-1950nm			2- 2W	2- 2kW	O-10/130 DC Fiber	L- Loose Tube	10-1.0m	FC/APC=FC/APC Connector
2000-2000nm			5- 5W	5- 5kW	Blank for SMF-28 Fiber	2- 2mm Cable	15-1.5m	LC/PC=LC/PC Connector
2050-2050nm			10-10W	10-10kW		3- 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector