

## 2000nm 1x6/2x6 High Power Fused Fiber Splitter Module

### FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

### APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



### SPECIFICATIONS

Parameter	Unit	1X6/2x6
Center Wavelength	nm	1900, 1950, 2000, 2050
Passband Width	nm	+/-20
Insertion Loss	dB	≤9.9
PDL	dB	≤0.3
Uniformity	dB	≤1.8
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 25, 30, 40, 50, 60, 80, 100
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
  5. Package size may be different for different optical power and fiber type.

### ORDERING INFORMATION (PN)

FCLT- <b>NNNN</b>	- <b>NXXN</b>	-HP <b>NN</b>	- ( <b>C</b> )	<b>C</b>	<b>NN</b>	- <b>CC/CCC</b>
Center Wavelength	Configuration	Optical Power	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1900=1900nm	1X6= 1x6 Type	1= 1W	V=SM1950 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
1950=1950nm	2X6= 2x6 Type	2= 2W	O=10/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
2000=2000nm		5= 5W	Blank for SMF-28 Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
2050=2050nm		10=10W		3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector