

915nm 1x6/2x6 High Power Fused Fiber Splitter Module

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	1X6/2x6
Center Wavelength	nm	915, 930, 940, 950
Passband Width	nm	+/-10
Insertion Loss	dB	≤10.3
PDL	dB	≤0.3
Uniformity	dB	≤1.8
Optical Return Loss	dB	≥40
Directivity	dB	≥50
Fiber Type	-	HI780C Fiber, HI1060 Fiber (H) or HI1060 Flex Fiber (F) 10/125um SC Fiber (E) or 10/125um DC Fiber (O)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 25, 30, 40, 50, 60, 80, 100
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(L)100x(W)80x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FCLT- NNN	- NXN	-HP NN	- (C)	C	NN	- CC/CCC
Center Wavelength	Configuration	Optical Power	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915=915nm	1X6= 1x6 Type	1= 1W	H= HI1060 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
930=930nm	2X6= 2x6 Type	2= 2W	E= 10/125SC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
940=940nm		5= 5W	O= 10/125DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
950=950nm		10=10W	Blank for HI780C Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector