

## 1064nm Faraday Mirror

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

### APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

### SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	1064
Bandwidth	nm	+/-5
Insertion Loss (Max.)	dB	3.4
Faraday Rotation Angle (Single Pass)	Deg	22.5, 45, 90
Rotation Angle Tolerance (1064nm, 23°C)	Deg	+/-3
PDL (for SM Fiber Type)	dB	≤0.05
Extinction Ratio (for PM Fiber Type)	dB	≥20
Fiber Type	SM Fiber Type	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
	PM Fiber Type	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	150
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	(Φ)5.5x35

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

<b>FFDM-</b>	<b>NNNN</b>	<b>- (NN)</b>	<b>- C</b>	<b>(C)</b>	<b>C</b>	<b>NN</b>	<b>- CC/CCC</b>
<i>Center Wavelength</i>	<i>Rotation Angle</i>	<i>Fiber Type</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>	
1064=1064nm	90= 90degree	P= PM Fiber	E=10/125 SC or PM1060L Fiber	B= Bare Fiber	05=0.5m	N=Without Connector	
	225=22.5degree	S=SM Fiber	Q=20/130 DC or PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector	
	Blank for 45degree		R=25/250 DC or PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector	
			Blank for HI1060 or PM980 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector	