

1625~1650nm Faraday Mirror

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength (λ_c)	nm	1625, 1650	
Bandwidth	nm	+/- 10	
Insertion Loss	(Typ.)	0.6	
	(Max.)	1.0	
Faraday Rotation Angle (Single Pass)	Deg	22.5, 45, 90	
Rotation Angle Tolerance (23°C, λ_c +/-15nm)	Deg	\leq +/-5	
Polarization Dependent Loss (SM Fiber Type)	dB	\leq 0.10	
Extinction Ratio (PM Fiber Type)	ps	\geq 20	
Fiber Type	SM Fiber Type	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)	
	PM Fiber Type	PM1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Φ)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFDM- NNNN	-	(NN)	-	C	(C)	(C)	C	NN	-	CC/CCC
<i>Center Wavelength</i>		<i>Rotation Angle</i>		<i>Fiber Type</i>	<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
1625~ 1625nm		90= 90degree		P= PM Fiber	M= Metal Box	O=10/130DC Fiber	B= Bare Fiber	05=0.5m		N=Without Connector
1650~ 1650nm		225=22.5degree		S=SM Fiber	Blank for SST	T=12/130DC Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
		Blank for 45degree				G=25/300 DC Fiber	2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
						Blank for SMF-28 Fiber or PM1550 Fiber	3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector