

1020~1080nm Optical Filter Coupler

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	1x2 Type			2x2 Type		
Center Wavelength	nm	1020, 1030, 1040, 1053, 1064, 1080					
Bandwidth	nm	+/-20nm or customer specify					
Split Ratio	-	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	1±0.5%	2±0.6%	5±1.0%	10%	40%	50%
Excess Loss	Max.	dB			1.0		
Uniformity	Max.	dB			0.6		
PDL	dB	≤0.15					
Optical Return Loss	dB	≥50					
Fiber Type	Tap Port	Same Fiber or 50/125um MM Fiber					
	Thru Port	HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)					
Fiber Tensile Load	N	5					
Max. Optical Power (CW)	mW	300					
Operating Temperature	°C	0~50					
Storage Temperature	°C	-40~85					
Package	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35				
Dimension	Metal Box	mm	^L 120x ^W 12x ^H 10				

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFC	-	NNNN	-	NN	N	(C)	-	(C)	(C)	C	NN	-	CC/CCC
<i>Wavelength</i>		<i>Split Ratio</i>		<i>Type</i>	<i>Tap Port Fiber</i>	<i>Package</i>		<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>		
1030=1030nm		01=1/99		1=1x2 Type	5=50/125um Fiber	M=Metal Box		E=10/125 SC Fiber	B= Bare fiber	05=0.5m	N=Without Connector		
1053=1053nm		05=5/95		2=2x2 Type	Blank for Same Fiber	Blank for SST		Q=20/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector		
1064=1064nm		10=10/90						R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector		
1080=1080nm		50=50/50						Blank for HI1060 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector		