

980nm High Power Filter Coupler

FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



SPECIFICATIONS

Parameter		Unit	1x2 Type				2x2 Type		
Center Wavelength		nm	980						
Bandwidth		nm	+/-15nm or customer specify						
Split Ratio		-	0.1:99.9	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio		-	0.1%	0.1%	2+/-0.6%	5+/-1.0%	10%	40%	50%
Excess Loss	Max.	dB	1.4				1.6		
Uniformity	Max.	dB	0.8				1.0		
PDL		dB	≤0.15						
Optical Return Loss		dB	≥50						
Fiber Type		-	HI HI1060 Fiber or 10/125um SC Fiber (E) 10/125um DC Fiber (O), 15/130um DC Fiber (W) 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)						
Fiber Tensile Load		N	5						
Max. Optical Power (CW)		W	1, 2, 3, 5, 10, 20						
Operating Temperature		°C	0~50						
Storage Temperature		°C	-40~85						
Package	Stainless Steel Tube (SST)	mm	(Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)						
Dimension	Metal Box	mm	(L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)						

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFFC-NNN	- NN	N	(C)	-HP NN	- (C)	(C)	C	NN	- CC/CCC
Wavelength	Split Ratio	Type	Tap Port Fiber	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
980-980nm	01-1/99	1-1x2	5-50/125um Fiber	1-1W	M-Metal Box	E-10/125 SC Fiber	B-Bare fiber	05-0.5m	N-Without Connector
	05/5/95	2-2x2	Blank for same Fiber	2-2W	Blank for SST	Q-20/130 DC Fiber	L-Loose Tube	10-1.0m	FC/APC=FC/APC Connector
	10-10/90			5-5W	or >10W	R-25/250 DC Fiber	2-2mm Cable	15-1.5m	LC/PC=LC/PC Connector
	50-50/50			10-10W		Blank for HI1060 Fiber	3-3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector