

915/1020~1120nm High Power WDM/Partial Mirror Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Signal Wavelength Range λ_1	nm	1020 \pm 5, 1030 \pm 10, 1040 \pm 10, 1053 \pm 10, 1064 \pm 10, 1080 \pm 10, 1092 \pm 5, 1120 \pm 5	
Pump Wavelength Range λ_2	nm	915 \pm 10	
Excess Loss	Signal Channel@ λ_1	dB	\leq 1.4
Insertion Loss	Pump Channel@ λ_2	dB	\leq 1.0
Signal Reflective Ratio (Common \leftrightarrow Pass)		%	1 \pm 0.6, 2 \pm 0.8, 5 \pm 1, 10, 20, 30, 40, 50, 60, 70, 80, 90
Wavelength	Signal Channel@ λ_2	dB	\geq 25
Isolation	Pump Channel@ λ_1	dB	\geq 12
Optical Return Loss		dB	\geq 45
PDL		dB	\leq 0.2
Pump Type	Forward	-	Pump&Signal at same direction
	Backward	-	Pump&Signal at reverse direction
Fiber Type	Common & Signal Port	-	HI780 Fiber, HI1060 Fiber or 10/125um SC Fiber (E)
		-	10/125um DC Fiber (O), 15/130um DC Fiber (W)
	Pump Port	-	20/130um DC Fiber (Q) or 25/250um DC Fiber (R)
		-	Same Fiber, HI780 Fiber or HI1060 Fiber
Fiber Tensile Load		N	5
Maximum Optical Power (CW)		W	1, 2, 3, 5, 10, 15, 20
Operating Temperature		$^{\circ}$ C	0~50
Storage Temperature		$^{\circ}$ C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x40 (\leq 5W); (\varnothing)6.0x48 (5~10W)
	Metal Box	mm	(L)90x(W)18x(H)10 (>10W); (L)120x(W)12x(H)10 (\leq 10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FFHP-91NN	- (C)	NN	(C)	-HP NN	-(C)	(C)	C	NN	-CC/CCC
Pass Wavelength	Pump Type	Refl. Ratio	Pump Fiber	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
06=1064nm	F= Forward	01= 1%	H=HI780 Fiber	1= 1W	M=Metal Box	H=HI1060 Fiber	B= Bare fiber	05=0.5m	N=Without Connector
03=1030nm	Blank for Backward	05=5%	Blank for Same Fiber	5= 5W	Blank for SST	E=10/125 SC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
08=1080nm		10=10%		10=10W	or >10W	R=25/250 DC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
12=1120nm		50=50%		20=20W		Blank for HI780 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector