

## 2000nm Partial Reflective Fiber Mirror for Pulse Power

### FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- Low Polarization Sensitivity
- Low Profile Packaging

### APPLICATIONS

- Fiber Optic Amplifiers
- Sensing Systems
- Telecommunication Networks
- CATV Networks
- LAN Systems

### SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength (CW)	nm	1900, 1950, 2000, 2050
Bandwidth	nm	+/-20
Excess Loss	dB	≤1.0
Nominal Reflective Ratio	%	1±0.5, 2±0.8, 5±1, 10±2, 50±8, 80, 90, 99
PDL (for SM Fiber Type)	dB	≤0.15
Extinction Ratio (for PM Fiber Type)	dB	≥18
Fiber Type	SM Fiber Type	-
	PM Fiber Type	-
Fiber Tensile Load	N	5
Max. Average Optical Power	W	0.3, 0.5, 1, 2, 3, 5, 10
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 20
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm
	Metal Box	mm

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
  3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

FFPF-NNNN	-	NN	C	C	-H NN	P NN	-(C)	(C)	C	NN	-CC/CCC
Center Wavelength	Ref. Ratio	Input Fiber	Output Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
1900-1900nm	01-1%	S=SM Fiber	S=SM Fiber	03-300mW	01-100W	M=Metal Box	V=SM1950 Fiber	B= Bare Fiber	05-0.5m	N=Without Connector	
1950-1950nm	10-10%	P= PM Fiber	P= PM Fiber	1-1W	1-1kW	Blank for SST	O=10/130 DC Fiber	L= Loose Tube	10-1.0m	FC/APC=FC/APC Connector	
2000-2000nm	50-50%			2-2W	5-5kW		R=25/250 DC Fiber	2= 2mm Cable	15-1.5m	LC/PC=LC/PC Connector	
2050-2050nm	80-80%			10-10W	10-10kW		Blank for SMF-28 Fiber or PM1550 Fiber	3= 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector	