

980/1020-1150nm WDM Filter for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs




SPECIFICATIONS

Parameters	Unit	Standard	High Isolation	
Pass Channel Wavelength Range λ_1	nm	980 \pm 10, 1020 \pm 5, 1030 \pm 10, 1040 \pm 10, 1053 \pm 10, 1064 \pm 10, 1070 \pm 10, 1080 \pm 10, 1092 \pm 5, 1120 \pm 5, 1150 \pm 5		
Reflective Channel Wavelength Range λ_2	nm			
Insertion Loss	Pass Channel@ λ_1	dB		
	Reflective Channel@ λ_2	dB		
Configuration	Y Type	-		
	X Type	-		
Isolation	Pass Channel@ λ_2	dB	dB	
	Reflective Channel@ λ_1	dB	dB	
Optical Return Loss		dB		
Directivity		dB		
Polarization Dependent Loss		dB		
Fiber Type		-		
		HI1060 Fiber or 10/125um SC Fiber (E)		
		10/125um DC Fiber (O), 15/130um DC Fiber (W) or 20/130um DC Fiber (Q) or 25/250um DC Fiber (R)		
Fiber Tensile Load	N	N		
Max. Average Optical Power	W	W		
Max. Peak Power for pulse	kW	kW		
Operating Temperature	°C	°C		
Storage Temperature	°C	°C		
Package Dimension	Stainless Steel Tube (SST)	mm	mm	
	Metal Box	mm	mm	

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.5dB higher, RL is 5dB lower.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different fiber type, optical power and configurations.

PACKAGE DIMENSION (> 10W)



ORDERING INFORMATION (PN)

Ref Wavelength	Pass Wavelength	Mode	Configuration	Isolation	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
03= 1030nm	98=980nm	M= Mux	X=X Type	I= High Iso	03=300mW	01=100W	M= Metal Box	E=10/125 SC Fiber	B= Bare Fiber	05=0.5m	N= Without Connector
06= 1064nm	04= 1040nm	D= Demux	Blank for Y Type	Blank for	1= 1W	1= 1kW	Blank for SST	Q=20/130 DC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
12=1120nm	07= 1070nm	Blank for Both		Standard	10=10W	10=10kW	or >10W	R=25/250 DC Fiber	2=2mm Cable	15=1.5m	LC/PC=LC/PC Connector
98=980nm	09=1092nm				20=20W	20=20kW		Blank for HI1060 Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

