

2090nm Polarization Beam Combiner(Splitter)/Isolator Hybrid

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Transmitters and Fiber Lasers
- CATV Networks



SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength (λ_c)	nm	2090	
Isolation ($\lambda_c \pm 10\text{nm}$, 23°C)	dB	≥ 16	≥ 30
Insertion Loss (λ_c , 23°C)	dB	≤ 1.5	≤ 2.0
Insertion Loss ($\lambda_c \pm 10\text{nm}$, 23°C)	dB	≤ 2.4	≤ 2.9
Optical Return Loss (Input/Output)	dB	50/45	50/45
Extinction Ratio	dB	≥ 18	
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1
Fiber Type of Port1 & Port2	-	PM1550 Panda Fiber or PM1950 Fiber (V) 10/130um PMDC Fiber (O) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-20~75	
Package	Stainless Steel Tube (SST)	mm	(Φ)5.5x35
Dimension	Metal Box-M	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN) FHIC=PBC/Isolator Hybrid; FHIS=PBS/Isolator Hybrid.

FHIC	-NNNN	- C	C	-(C)	C	C	NN	-CC/CCC
FHIS								
	Center Wavelength	Stage	3rd Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
	2090-2090nm	S= Single Stage D= Dual Stage	S=S Type P=P Type Q=Q Type	M=Metal Box Blank for SST	2=PM1550Fiber V=PM1950 Fiber O=10/130 PMDC Fiber R=25/250 PMDC Fiber	B= Bare fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector