

Optical Inline Polariser for Pulse Power



FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation

SPECIFICATIONS

Parameter		Unit	Value
Center Wavelength		nm	1310, 1480, 1550, 1590
Bandwidth		nm	+/-30
Insertion Loss @ 23°C	(Typ.)	dB	0.5
	(Max.)	dB	0.8
Extinction Ratio @ 23°C	(Typ.)	dB	26
	(Min.)	dB	23
Optical Return Loss		dB	≥50
Configuration	D Type	-	2-port, Standard
	Y Type	-	3-port, Fast axis blocked light guide out
Fiber Type at 3 rd Port (Only for Y Type)		-	Same Fiber, Corr. SM Fiber or 50/125um MM Fiber
Fiber Type	SM Fiber	-	SMF-28 Fiber or 10/130um DC Fiber (O) 12/130um DC Fiber (T) or 20/130um DC Fiber (Q) 25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	PM Fiber	-	PM1310/1550 Panda Fiber, 10/125um PMDC Fiber (O), 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R), 25/300um PMDC Fiber (G)
Fiber Tensile Load		N	5
Max. Average Optical Power		W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20
Max. Peak Power for pulse		kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature		°C	0~70
Storage Temperature		°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)
	Metal Box	mm	(L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Suggest to use Y type if blocked optical power is >1W.
 4. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 5. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FILP-NNNN	- C	C	(C)	-H	NN	P NN	-(C)	(C)	C	NN	- CC/CCC
Center Wavelength	Input Fiber	Output Fiber	3rd Port Fiber	Average Power	Peak Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
1310-1310nm	P= PM Fiber	P= PM Fiber	P= Same Fiber	03-300mW	01-100W	M= Metal Box	O=10/130 DC Fiber	B= Bare fiber	05-0.5m	N= Without Connector	
1480-1480nm	S= SM Fiber	S= SM Fiber	S= Corr. SM Fiber	1- 1W	1- 1kW	Blank for SST	T=12/130 DC Fiber	L= Loose Tube	10-1.0m	FC/APC=FC/APC Connector	
1550-1550nm			S=50/125um MM Fiber	5- 5W	5- 5kW	or >10W	G=25/300 DC Fiber	2= 2mm Cable	15-1.5m	LC/PC=LC/PC Connector	
1590-1590nm			Blank for D Type	10-10W	10-10kW		Blank for SMF-28 Fiber	3= 3mm Cable	20-2.0m	SC/UPC=SC/UPC Connector	

or PM1310/1550 Fiber

