

2090nm Inline Optical Isolator

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength (λ_c)	nm	2090	
Isolation ($\lambda_c \pm 10\text{nm}$, 23°C)	dB	≥ 16	≥ 25
Insertion Loss (λ_c , 23°C)	dB	≤ 1.6	≤ 2.2
Insertion Loss ($\lambda_c \pm 10\text{nm}$, 23°C)	dB	≤ 2.0	≤ 2.5
Optical Return Loss (Input/Output)	dB	50/45	50/45
PDL	dB	≤ 0.2	
Fiber Type	-	SMF-28 Fiber or SM1950 Fiber (V) 10/130um DC Fiber (O) or 25/250um DC Fiber (R)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-20~75	
Package	Stainless Steel Tube (SST)	mm	$\Phi 5.5 \times L 35$
Dimension	Metal Box-M	mm	$L 120 \times W 12 \times H 10$

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 5dB lower.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FISO-NNNN	-	C	-	(C)	C	NN	-	CC/CCC
<i>Center Wavelength</i>		<i>Stage</i>		<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>		<i>Fiber Length</i>
2090-2090nm		S= Single Stage D= Dual Stage		M= Metal Box Blank for SST	V= SM1950 Fiber O= 10/130 DC Fiber R= 25/250 DC Fiber Blank for SMF-28 Fiber	B= Bare fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable		05=0.5m 10=1.0m 15=1.5m 20=2.0m
								<i>Connector Type</i>
								N= Without Connector FC/APC= FC/APC Connector LC/PC= LC/PC Connector SC/UPC= SC/UPC Connector