

1030nm Multimode Bandpass Filter for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1030	
Min. Pass Band Width @ 0.5dB	nm	1.3, 2.0, 4.0, 6.0, 9.0, 10, 12, 20	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop Wavelength (ASE)	1.3nm Bandwidth	nm	1000~1027&1033~1100
	2nm Bandwidth	nm	1000~1027&1033~1100
	4nm Bandwidth	nm	1000~1024&1034~1100
	6nm Bandwidth	nm	1000~1024&1036~1100
	9nm Bandwidth	nm	1000~1022&1038~1100
	10nm Bandwidth	nm	1000~1021&1039~1100
	12nm Bandwidth	nm	1000~1018&1042~1100
Stop Wavelength (ASE) Isolation	Standard	dB	≥25
	High Isolation	dB	≥45
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥30	
Fiber Type	Input&Output	-	50/125um (OM2) or 62.5/125um (OM1) MM Fiber 50/125um OM3 MM Fiber (3) or OM4 MM Fiber(4) 105/125um MM Fiber, NA=0.12(C), 0.15(B),
	ASE Guide Out (Y/X Type)	-	Same Fiber
Fiber Tensile Load	N	5	
Max. Average Optical Power (ASE+Signal)	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 30, 50, 60, 80, 100	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Max. ASE Average Power	W	0.3, 0.5, 1, 2, 3, 4, 5, 10	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)
	Metal Box	mm	H: ^L 90x ^W 12x ^H 10 (>10W); M: ^L 120x ^W 12x ^H 10

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 - Specifications are tested at low order modes.
 - Suggest to use Y/X type if blocked optical power is ≥1W.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FMBP-1030-NN(C) (C)-(C) (C) - HNN PNN - (NN) -(C) C C NN - CC/CC

Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Dwd ASE Fiber	Average Power	Peak Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
20~2nm	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	03~300mW	01~100W	1~1W	M=Metal Box	5= 50/125um MM Fiber	B= Bare fiber	05=0.5m	N=Without Connector
60~6nm	T=Two-way	Isolation	N=None	Blank for None/D Type	1~1W	1~1kW	5~5W	H=H Box	6= 62.5/125um MM Fiber	L= Loose Tube	10~1.0m	FC/APC=FC/APC Connector
90~9nm	Blank for Forward	Blank for	Blank for D Type		5~5W	10~10kW	10~10W	Blank for SST	A= 105/125um, NA=0.22	2= 2mm Cable	15~1.5m	LC/PC=LC/PC Connector
200~20nm		Standard			20~20W	20~20kW	Blank for 300mW		B=105/125um, NA=0.15	3= 3mm Cable	20~2.0m	SC/UPC=SC/UPC Connector