

## 1092nm Multimode Bandpass Filter for Pulse Power

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1092	
Min. Pass Band Width @ 0.5dB	nm	8.0	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop Wavelength (ASE)	nm	1000~1084&1100~1150	
Stop Wavelength (ASE) Standard	dB	≥25	
Isolation High Isolation	dB	≥45	
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥30	
Fiber Type	Input&Output	-	50/125um or 62.5/125um MM Fiber
		-	50/125um MM OM3 Fiber
		-	105/125um MM Fiber
	ASE Guide Out (Y/X Type)	-	Same Fiber
Fiber Tensile Load	N	5	
Max. Average Optical Power (ASE+Signal)	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 30, 50, 60, 80, 100	
Max. Peak Power for pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20	
Max. ASE Average Power	W	0.3, 0.5, 1, 2, 3, 4, 5, 10	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x <sup>L</sup> 35 (≤5W); ∅6.0x <sup>L</sup> 50 (5~10W)
	Metal Box	mm	<sup>L</sup> 90x <sup>W</sup> 12x <sup>H</sup> 10 (>10W); <sup>L</sup> 120x <sup>W</sup> 12x <sup>H</sup> 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
  - To add connectors, IL is 0.3dB higher, RL is 10dB lower.
  - Specifications are tested at low order modes.
  - Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
  - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
  - Devices for higher optical power or with other type fiber or consigned fiber are also available.
  - Package size may be different for different fiber type, optical power and configurations.

### ORDERING INFORMATION (PN)

**FMBP-1092-NN(C) (C) (C) (C) - H NN P NN - (NN) -(C) C C NN - CC/CCC**

Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Average Power	Peak Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
80~8nm	B=Backward T=Two-way Blank for Forward	I=High Isolation Blank for	Y=Same Fiber N=None Blank for D Type Standard	Y=Same Fiber Blank for None or D Type	03=300mW 1=1W 5=5W 20=20W	01=100W 1=1kW 10=10kW 20=20kW	1=1W 5=5W 10=10W Blank for 300mW	M=Metal Box H=H Box Blank for SST	5=50/125um MM Fiber 6=62.5/125um MM Fiber 3=OM3 MM Fiber A=105/125um, NA=0.22 B=105/125um, NA=0.15	B= Bare fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector

