

1556nm Multimod Bandpass Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1556	
Min. Pass Band Width @ 0.5dB	nm	0.12, 0.3, 0.7, 2.5, 8.0, 20	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop Wavelength (ASE)	0.12nm Bandwidth	1500~1555.4 & 1556.6-1610	
	0.3nm Bandwidth	1500~1555 & 1557-1610	
	0.7nm Bandwidth	1500~1554.5 & 1557.5-1610	
	2.5nm Bandwidth	1500~1553 & 1559-1610	
	8nm Bandwidth	1500~1548 & 1564-1610	
Stop Wavelength (ASE)	Standard	≥25	
Isolation	High Isolation	≥45	
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥30	
Fiber Type	Input&Output	50/125um (OM2) or 62.5/125um (OM1) MM Fiber 50/125um OM3 MM Fiber (3) or OM4 MM Fiber(4) 105/125um MM Fiber, NA=0.12(C), 0.15(B), 0.22(A)	
	ASE Guide Out (Y/X Type)	Same Fiber	
Fiber Tensile Load	N	5	
Max. Optical Power (CW, ASE+Signal)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35
	Metal Box	mm	^L 120x ^W 12x ^H 10

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.

3. Specifications are tested at low order modes.

4. Devices for higher optical power or with other type fiber or consigned fiber are also available.

5. Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FMBP-1556-NN(C)	(C)	(C)	(C)	-(C)	C	C	NN	- CC/CCC	
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
03=0.3nm	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	M=Metal Box	5= 50/125um MM Fiber	B= Bare fiber	05=0.5m	N=Without Connector
25=2.5nm	T=Two-way	Isolation	N=None	Blank for None or D Type	Blank for SST	6= 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
80=8nm	Blank for Forward	Blank for	Blank for D Type			3= OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
200=20nm		Standard				A= 105/125um, NA=0.22	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector

