

## 1590nm Multimode Bandpass Filter

### FEATURES

- ▣ High Isolation
- ▣ Low Insertion Loss
- ▣ High Reliability and Stability
- ▣ Various Bandwidth
- ▣ High Optical Power

### APPLICATIONS

- ▣ Broadband Systems
- ▣ Optical Amplifying Systems
- ▣ Telecommunication Networks
- ▣ Laser Systems
- ▣ Research Labs



### SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	1590	
Min. Pass Band Width @ 0.5dB	nm	0.3, 0.7, 1.3	
Insertion Loss over Pass Band Wavelength	dB	≤1.2	
Stop Wavelength (ASE)	0.3nm Bandwidth	nm	1530~1589 & 1591~1630
	0.7nm Bandwidth	nm	1530~1588.5 & 1591.5~1630
	1.3nm Bandwidth	nm	1530~1587.5 & 1592.5~1630
Stop Wavelength (ASE)	Standard	dB	≥25
Isolation	High Isolation	dB	≥45
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥30	
Fiber Type	Input&Output	-	50/125um (OM2) or 62.5/125um (OM1) MM Fiber 50/125um OM3 MM Fiber (3) or OM4 MM Fiber(4) 105/125um MM Fiber, NA=0.12(D), 0.15(B), 0.22(A)
	ASE Guide Out (Y/X Type)	-	Same Fiber
Fiber Tensile Load	N	5	
Max. Optical Power (CW, ASE+Signal)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5xL35
	Metal Box	mm	L120xW12xH10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
  2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
  3. Specifications are tested at low order modes.
  4. Devices for higher optical power or with other type fiber or consigned fiber are also available.
  5. Package size may be different for different optical power and configurations.

### ORDERING INFORMATION (PN)

FMBP-1590-NN(C) (C) - (C) (C) -(C) C C NN -CC/CCC									
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
03-0.3nm	B-Backward	I-High	Y-Same Fiber	Y-Same Fiber	N-Metal Box	5- 50/125um MM Fiber	B- Bare fiber	05-0.5m	N-Without Connector
07-0.7nm	T-Two-way	Isolation	N=None	Blank for None or D Type	Blank for SST	6- 62.5/125um MM Fiber	L- Loose Tube	10-1.0m	FC/APC-FC/APC Connector
13-1.3nm	Blank for Forward	Blank for	Blank for D Type			3- OM3 MM Fiber	2- 2mm Cable	15-1.5m	LC/PC-LC/PC Connector
		Standard				A- 105/125um, NA=0.22	3- 3mm Cable	20-2.0m	SC/UPC-SC/UPC Connector
						B-105/125um, NA=0.15			