

Multimode 1x3 Fused Fiber Splitter

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments

SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	850, 1300
Split Ratio	%	33.3:33.3:33.3
Insertion Loss	dB	≤6.5
Uniformity	dB	≤1.2
Directivity	dB	≥40
Fiber Type	-	50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fibe
Fiber Tensile Load	N	5
Maximum Optical Power	mW	300
Operating Temperature	°C	0~70
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube	mm (Φ)3.0x60
	Metal Box	mm (L)98x(W)18x(H)8.5
	Plastic Box	mm (L)88.9x(W)50.9x(H)9.2

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Specifications are tested at low order modes.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available.

ORDERING INFORMATION (PN)

FMCL	-	NNNN	-	NXN	C	-	N	C	NN	-	CC/CCC
Center Wavelength		Configuration		Package	Fiber Type		Fiber Sleeve		Fiber Length		Connector Type
850= 850nm		1X3= 1x3 Type		S=SSL Tube	5=50/125um MM Fiber		B= 250um Bare Fiber		10=1.0m		N =Without Connector
1300= 1300nm				M= Metal Box	6= 62.5/125um MM Fiber		L= 900um Loose Tube		15=1.5m		FC/APC=FC/APC Connector
				P=Plastic Box	3= OM3 MM Fiber		3=3mm Cable		20=2.0m		LC/PC =LC/PC Connector