

915/980nm High Power Multimode Filter Coupler

FEATURES

- Low Excess Loss
- Various Splitting Ratio
- Wide Passband
- High Stability and Reliability
- Epoxy Free Optical Path

APPLICATIONS

- Optical Amplifier
- Optical Networks
- Power Monitoring
- Fiber Sensor
- Lab



SPECIFICATIONS

Parameter	Unit	1x2 Type			2x2 Type			
Center Wavelength	nm	915, 980						
Bandwidth	nm	+/-15nm or customer specify						
Split Ratio	-	0.1:99.9	1:99	2:98	5:95	10:90	40:60	50:50
Tap Ratio	-	0.1%	1+/-0.5%	2+/-0.6%	5+/-1.0%	10%	40%	50%
Excess Loss Max.	dB	1.2			1.5			
Uniformity Max.	dB	0.8			1.0			
Optical Return Loss	dB	≥35						
Fiber Type	-	50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fiber 105/125um MM Fiber						
Fiber Tensile Load	N	5						
Max. Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20, 25, 30						
Operating Temperature	°C	0~50						
Storage Temperature	°C	-40~85						
Package	Stainless Steel Tube (SST)	mm	(Ø)5.5x35 (≤5W); (Ø)6.0x48 (5~10W)					
Dimension	Metal Box	mm	(L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)					

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Specifications are tested at low order modes.
 5. Devices with other wavelength range are also available per request.
 6. Devices for higher optical power or with other type fiber or consigned fiber are also available.

ORDERING INFORMATION (PN)

FMFC-NNN	- NN	N	-HP NN	- (C)	N	C	NN	- CC/CCC
Wavelength	Split Ratio	Type	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
915=915nm	01=1/99	1=1x2	1=1W	M=Metal Box	5= 50/125um MM Fiber	B= Bare fiber	05=0.5m	N=Without Connector
980=980nm	05=5/95	2=2x2	2=2W	Blank for SST	6= 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	10=10/90		10=10W	or >10W	3= OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	50=50/50		25=25W		A= 105/125um, NA=0.22	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector
					B=105/125um, NA=0.15			