

780~850/1300~1590nm Multimode WDM Filter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Add/Drop Multiplexing
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Value	
Pass Channel Wavelength Range λ_1	nm	1300+/-20, 1550+/-20, 1590+/-20	
Reflective Channel Wavelength Range λ_2	nm	780+/-10, 793+/-10, 808+/-10, 830+/-10, 850+/-10	
Insertion Loss	Pass Channel@ λ_1	dB	≤ 1.2
	Reflective Channel@ λ_2	dB	≤ 1.0
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation	Pass Channel@ λ_2	dB	≥ 25
	Reflective Channel@ λ_1	dB	≥ 12
Optical Return Loss		dB	≥ 30
Directivity		dB	≥ 35
Fiber Type	-		50/125um or 62.5/125um MM Fiber 50/125um MM OM3 Fiber 105/125um MM Fiber
Maximum Optical Power (CW)	mW		300
Operating Temperature	°C		0~50
Storage Temperature	°C		-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available.
 4. Specifications are tested at low order modes.
 5. Devices with other wavelength range are also available per request.

ORDERING INFORMATION (PN)

Ref Wavelength	Pass Wavelength	Configuration	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
78- 780nm	15- 1550nm	X= X Type	M= Metal Box	5- 50/125um MM Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
81- 808nm	13-1300nm	Blank for Y Type	Blank for SST	6- 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
83- 830nm	59- 1590nm		or >10W	3- OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
85- 850nm				A= 105/125um, NA=0.22 B=105/125um, NA=0.15	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector