

1080nm PM Bandpass Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

| Parameters | | Unit | Standard | High ER Type |
|--|----------------------------|------|--|--------------|
| Center Wavelength | | nm | 1080 | |
| Min. Pass Band Width @ 0.5dB | | nm | 5.0 | |
| Insertion Loss over Pass Band Wavelength | | dB | ≤1.2 | ≤1.4 |
| Stop Wavelength (ASE) | | nm | 1030-1070&1090-1150 | |
| Stop Wavelength (ASE) | Standard | dB | ≥25 | |
| Isolation | High Isolation | dB | ≥45 | |
| ASE Direction | | - | F: Forward, B: Backward, T: Two-way | |
| Configuration | | - | D: 2-port, Y: 3-port, X: 4-port | |
| Optical Return Loss | | dB | ≥50 | |
| Extinction Ratio | | dB | ≥18 | ≥20 |
| Fiber Type | Input&Output | - | PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R) | |
| | ASE Guide Out (Y/X Type) | - | Same Fiber, Corr. SM Fiber or MM Fiber | |
| Fiber Tensile Load | | N | 5 | |
| Max. Optical Power (CW, ASE+Signal) | | mW | 300 | |
| Operating Temperature | | °C | 0~50 | |
| Storage Temperature | | °C | -40~85 | |
| Package Dimension | Stainless Steel Tube (SST) | mm | ∅5.5x ^L 35 | |
| | Metal Box | mm | ^L 120x ^W 12x ^H 10 | |

Note: 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. High ER type can only work in slow axis.

4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

5. Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

| | | | | | | | | | | |
|----------------------------|-------------|-------------------|----------------|----------------------|--------------------------|----------------|---------------------|---------------------|---------------------|-------------------------|
| FPBP-1080-NN(C) (C) | | (C) | (C) | (C) | -(C) | C | C | NN | -CC/CCC | |
| <i>Bandwidth</i> | <i>Type</i> | <i>ASE Type</i> | <i>ASE Iso</i> | <i>Fwd ASE Fiber</i> | <i>Dwd ASE Fiber</i> | <i>Package</i> | <i>Fiber Type</i> | <i>Fiber Sleeve</i> | <i>Fiber Length</i> | <i>Connector Type</i> |
| 50=5nm | R=High ER | B=Backward | I=High | Y=Same Fiber | Y=Same Fiber | M=Metal Box | 2=PM980Fiber | B= Bare fiber | 05=0.5m | N=Without Connector |
| | Blank for | T=Two-way | Isolation | S=Corr. SM Fiber | S=Corr. SM Fiber | Blank for SST | E=PM1060L Fiber | L= Loose Tube | 10=1.0m | FC/APC=FC/APC Connector |
| | Standard | Blank for Forward | Blank for | N=None | A=105/125um Fiber | | Q=20/130 PMDC Fiber | 2= 2mm Cable | 15=1.5m | LC/PC=LC/PC Connector |
| | | | Standard | Blank for D Type | Blank for None or D Type | | R=25/250 PMDC Fiber | 3= 3mm Cable | 20=2.0m | SC/UPC=SC/UPC Connector |