

1020-1120/1310~1650nm Fused PM WDM Coupler

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- Research Labs
- Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Wavelength Range Channel 1 (λ_1)	nm	1020 \pm 10, 1030 \pm 10, 1040 \pm 10, 1053 \pm 10, 1064 \pm 10, 1070 \pm 10, 1080 \pm 5, 1092 \pm 5, 1100 \pm 5, 1120 \pm 5, 1150 \pm 5
Wavelength Range Channel 2 (λ_2)	nm	1310 \pm 5, 1550 \pm 10, 1590 \pm 10, 1625 \pm 10, 1650 \pm 10
Insertion Loss	dB	\leq 0.8
Isolation	dB	\geq 15
Extinction Ratio	dB	\geq 18
Optical Return Loss	dB	\geq 40
Directivity	dB	\geq 50
Fiber Type	-	PM980 Fiber (H) or 10/125um PMDC Fiber NA=0.08(O) PM1310/1550 Fiber or 8/125um PMDC Fiber NA=0.12(M)
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	$^{\circ}$ C	0~50
Storage Temperature	$^{\circ}$ C	-40~85
Package	Stainless Steel Tube (SST)	ϕ 3.0x ^L 60 for Bare Fiber
Dimension	Metal Box	ϕ 3.0x ^L 76 for 900um Loose Tube
		^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. 1020-1150nm transmits as low order modes in signal fiber
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

FPCD-NN	NN -	N	(C)	(C)	-(C)	(C)	C	NN	-CC/CCC
Wavelength1	Wavelength2	Configuration	Mode	Fiber(λ_1)	Package	Fiber (Com λ_2)	Fiber Sleeve	Fiber Length	Connector Type
03-1030nm	15-1550nm	1- 1x2 Type	M= Mux	S= Corr. SM Fiber	M= Metal Box	H= PM980 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
06-1064nm	13-1310nm	2- 2x2 Type	D= Demux	H= PM980 Fiber	Blank for SST	M= 8/125 PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
59-1590nm	09- 1092nm		Blank for Both	I=HI1060 Fiber		O= 10/125 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
62-1625nm	12-1120nm			Blank for Same Fiber		Blank for PM1310/1550 Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector