

406-690/1310~1650nm Fused PM WDM Coupler for Pulse Power

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Wavelength Range Channel 1 (λ_1)	nm	406 \pm 5, 460 \pm 5, 488 \pm 5, 520 \pm 10, 532 \pm 10, 635 \pm 10, 650 \pm 10, 660 \pm 10, 690 \pm 10
Wavelength Range Channel 2 (λ_2)	nm	1310 \pm 20, 1550 \pm 20, 1590 \pm 20, 1625 \pm 10
Insertion Loss @ λ_2	dB	\leq 1.0
Insertion Loss @ λ_1	dB	\leq 1.5
Isolation	dB	\geq 10
Extinction Ratio (λ_2)	dB	\geq 18
Optical Return Loss	dB	\geq 40
Directivity	dB	\geq 50
Fiber Type	Common&1.5um Port 0.5um Port	- - PM980 Fiber or PM1310/1550 Fiber Same Fiber, or PM460-HP Fiber/PM630-HP Fiber (P) Corr. SM Fiber (S) or 460-HP Fiber/630-HP Fiber (H)
Fiber Tensile Load	N	5
Max. Average Optical Power (λ_2)	W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 25, 30
Max. Average Optical Power (λ_1)	mW	30
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20
Operating Temperature	$^{\circ}$ C	0~50
Storage Temperature	$^{\circ}$ C	-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm ϕ 3.0x ^L 60 for Bare Fiber ϕ 3.0x ^L 76 for 900um Loose Tube ^L 120x ^W 12x ^H 10 for 2mm/3mm Cable

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.9dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 30mW continuous wave (CW) power thru testing for connectors added.
 - 406-690nm transmits as low order modes in signal fiber.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available.
 - Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN)

Wavelength1	Wavelength2	Configuration	Mode	Fiber(λ_1)	Average Power	Peak Power	Average Power(0.5um)	Package	Fiber (Com&2.2)	Fiber Sleeve	Fiber Length	Connector Type
406-406nm	15-1550nm	1- 1x2 Type	M= Mux	S= Corr. SM Fiber	03= 300mW	01= 100W	01= 100mW	M= Metal Box	H= PM980 Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
532-532nm	13-1310nm	2- 2x2 Type	D= Demux	P= PM460/PM630 Fiber	5=5W	5=5kW	05= 500mW	Blank for SST	Blank for	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
59-1590nm	635-635nm		Blank for Both	H=460HP/630HP Fiber	10=10W	10=10kW	1=1W		PM1310/1550 Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
62-1625nm	660-660nm			Blank for Same Fiber	30= 30W	20= 20kW	Blank for 30mW			3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector