

1600~1750nm 1x2/2x2 High Power Fused PM Coupler/Splitter

FEATURES

- Low Excess Loss
- Variety Coupling Ratio
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- LAN WAN Systems
- Signal Monitoring
- Network Monitoring
- CATV
- Test Equipments



SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	1600, 1650, 1700, 1750
Bandwidth	nm	+/-10
Excess Loss	dB	≤0.90
Tap Ratio	dB	1±0.5%, 2±0.8%, 5±1.5%, 10±2.3%, 50±5%
Directivity	dB	≥50
Extinction Ratio	dB	≥18
Fiber Type	-	PM1550 Panda Fiber
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	1, 2, 3, 5, 10, 15, 20, 25, 30
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm
		(Φ)3.0x60 for Bare Fiber
		(Φ)3.0x76 for 900um Loose Tube (L)120x(W)12x(H)10 for 2mm/3mm Cable

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. For 5%≤Tap Ratio≤10%, Tap Port ER is 2dB Lower, for 1%≤Tap Ratio<5%, Tap Port ER is 5dB Lower, for Tap Ratio<1%, Tap Port ER is out of concern.
 5. Devices for higher optical power or with other type fiber or consigned fiber are also available.

ORDERING INFORMATION (PN)

FPCL-	NNNN	-	NN		N	-HP	NN	-	(C)	C	NN	-	CC/CCC
Center Wavelength	Coupling Ratio.		Configuration	Optical Power	Package	Fiber Sleeve	Fiber Length		Connector Type				
1600-1600nm	01- 1% Ratio		1- 1x2 Type	1- 1W	M= Metal Box	B= Bare Fiber	05=0.5m		N =Without Connector				
1650- 1650nm	05- 5% Ratio		2- 2x2 Type	2- 2W	Blank for SSL Tube	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector				
1700-1700nm	10- 10% Ratio			10- 10W		2= 2mm Cable	15=1.5m		LC/PC =LC/PC Connector				
1750-1750nm	50- 50% Ratio			30-30W		3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector				