

1064nm 3-port PM Optical Circulator



FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Light Routing

SPECIFICATIONS

| Parameter | | Unit | A Type | B Type |
|-------------------------------|----------------------------|------|--|--------|
| Center Wavelength | | nm | 1064 | |
| Bandwidth | | nm | +/-5 | |
| Insertion Loss (1→2, 2→3) | (Typ.) | dB | 3.2 | 1.7 |
| | (Max.) | dB | 4.0 | 2.2 |
| Isolation@ 23°C (3→2, 2→1) | (Typ.) | dB | 50 | 28 |
| | (Min.) | dB | 45 | 22 |
| Cross Talk | | dB | ≥50 | |
| Optical Return Loss | | dB | ≥50 | |
| Extinction Ratio | (Typ.) | dB | 25 | 22 |
| | (Min.) | dB | 22 | 20 |
| Polarization Alignment | | - | Slow Axis | |
| Fiber Type | | - | PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O), 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R) | |
| Fiber Tensile Load | | N | 5 | |
| Maximum Optical Power (CW) | | mW | 300 | |
| Operating Temperature | | °C | 0~50 | |
| Storage Temperature | | °C | -40~85 | |
| Package Dimension | Stainless Steel Tube (SST) | mm | ∅5.5xL35 | |
| | Metal Box | mm | L120xW12xH10 | |

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. The devices can only work in slow axis and fast axis is blocked.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

| | | | | | | | |
|--------------|--------------------------|----------------------|------------------------------|---|--|--|--|
| FPCR- | NNNN | -3 C | - (C) | C | C | NN | - CC/CCC |
| | <i>Center Wavelength</i> | <i>Type</i> | <i>Package</i> | <i>Fiber Type</i> | <i>Fiber Sleeve</i> | <i>Fiber Length</i> | <i>Connector Type</i> |
| | 1064=1064nm | A=A Type B=B Type | M=Metal Box Blank for SST | 2=PM980Fiber E=PM1060L Fiber Q=20/130 PMDC Fiber R=25/250 PMDC Fiber | B= Bare Fiber L= Loose Tube 2= 2mm Cable 3= 3mm Cable | 05=0.5m 10=1.0m 15=1.5m 20=2.0m | N=Without Connector FC/APC=FC/APC Connector LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector |