

900~950nm 1x3 PM Filter Splitter Module

FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



SPECIFICATIONS

Parameter	Unit	Value
Center Wavelength	nm	915, 930, 940, 950
Bandwidth	nm	+/-15nm or customer specify
Configuration	-	1x3
Split Ratio	%	33.3/33.3/33.3
Insertion Loss	dB	≤6.4
Uniformity	dB	≤0.9
Extinction Ratio	dB	≥20
Optical Return Loss	dB	≥50
Working Mode	-	Can only work in Slow Axis
Fiber Type	-	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)
Alignment	-	Slow Axis
Fiber Tensile Load	N	5
Maximum Optical Power (CW)	mW	300
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	^L 160x ^W 140x ^H 10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. The devices can only work in slow axis and fast axis is blocked.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPFM-	NNN	-	1X3	-	C	C	NN	-	CC/CCC
	<i>Wavelength</i>				<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
	915~915nm				2~PM850Fiber	B~ Bare Fiber	05~0.5m		N~Without Connector
	930~930nm				H~PM980 Fiber	L~ Loose Tube	10~1.0m		FC/APC~FC/APC Connector
	940~940nm				E~PM1060L Fiber	2~ 2mm Cable	15~1.5m		LC/PC~LC/PC Connector
	950~950nm				R~25/250 PMDC Fiber	3~ 3mm Cable	20~2.0m		SC/UPC~SC/UPC Connector