

## 975~1160nm PM Filter Splitter Module

### FEATURES

- ▣ Low Excess Loss
- ▣ Various Splitting Ratio
- ▣ Wide Passband
- ▣ High Stability and Reliability
- ▣ Epoxy Free Optical Path

### APPLICATIONS

- ▣ Optical Amplifier
- ▣ Optical Networks
- ▣ Power Monitoring
- ▣ Fiber Sensor
- ▣ Lab



### SPECIFICATIONS

Parameter	Unit	1x4 or 2x4 or 4x4	1x8 or 2x8 or 4x8
Center Wavelength	nm	975, 980, 990, 1000 1020, 1030, 1040, 1053, 1064 1070, 1080, 1092, 1103, 1120, 1150	
Bandwidth	nm	+/-20nm or customer specify	
Insertion Loss	Typ.	7.2	10.8
	Max.	7.8	11.5
Uniformity	dB	≤1.0	≤1.2
Extinction Ratio	B Type	≥20	≥17
	F Type	≥22	
Working Mode	B Type	Can work both in Fast Axis and Slow Axis	
	F Type	Can only work in Slow Axis and Fast Axis is blocked	
Optical Return Loss	dB	≥50	
Directivity	dB	≥50	≥45
Fiber Type	-	PM980 Fiber, PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	mm	L160x <sup>W</sup> 140x <sup>H</sup> 10	L160x <sup>W</sup> 160x <sup>H</sup> 10

**Note:** 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.5dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

### ORDERING INFORMATION (PN)

<b>FPFM -</b>	<b>NNNN</b>	<b>-</b>	<b>NxN</b>	<b>(C)</b>	<b>-</b>	<b>C</b>	<b>C</b>	<b>NN</b>	<b>-</b>	<b>CC/CCC</b>
<i>Wavelength</i>	<i>Configuration</i>		<i>Type</i>	<i>Fiber Type</i>		<i>Fiber Sleeve</i>	<i>Fiber Length</i>	<i>Connector Type</i>		
975-975nm	1X4-1X4 Type		B=B Type	2-PM980Fiber		B= Bare Fiber	05=0.5m	N=Without Connector		
1030-1030nm	1X8-1X8 Type		Blank for F Type	E-PM1060L Fiber		L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector		
1064-1064nm	2X4-2X4 Type			Q=20/130 PMDC Fiber		2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector		
1120-1120nm	4X8-4X8 Type			R=25/250 PMDC Fiber		3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector		