

Polarization Maintaining Inline Optical Isolator

FEATURES

- ☑ High Isolation
- ☑ Low Insertion Loss
- ☑ Epoxy-Free Optical Path
- ☑ High Reliability and Stability
- ☑ Low Profile Packaging

APPLICATIONS

- ☑ Fiber Optic Amplifiers
- ☑ Fiber Optic Instruments
- ☑ WDM Systems
- ☑ Transmitters and Fiber Lasers
- ☑ CATV Networks



SPECIFICATIONS

Parameter	Unit	Single Stage	Dual Stage
Center Wavelength (λ_c)	nm	1310, 1480, 1550, 1590	
Peak Isolation (Typ.)	dB	42	58
Isolation ($\lambda_c \pm 15\text{nm}$, 23°C)	dB	≥ 28	≥ 45
Insertion Loss (λ_c , 23°C)	dB	≤ 0.4	≤ 0.5
Insertion Loss ($\lambda_c \pm 20\text{nm}$, 0-70°C)	dB	≤ 0.6	≤ 0.7
Optical Return Loss (Input/Output)	dB	55/50	55/50
Extinction Ratio	dB	≥ 20	
Working Mode	S Type	-	Can only work in Slow Axis
	F Type	-	Can work both in Slow Axis and Fast Axis
Fiber Type	-	PM1310/1550 Panda Fiber, 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R), 25/300um PMDC Fiber (G)	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	$\varnothing 5.5 \times L35$
	Metal Box	mm	$L120 \times W12 \times H10$

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPIS-NNNN	- C	C	-(C)	C	C	NN	- CC/CCC
Center Wavelength	Stage	Type	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1310-1310nm	S= Single Stage	S= S Type	M= Metal Box	2= PM1310/1550 Fiber	B= Bare Fiber	05= 0.5m	N= Without Connector
1550-1550nm	D= Dual Stage	F= F Type	Blank for SST	0= 10/125 PMDC Fiber	L= Loose Tube	10= 1.0m	FC/APC= FC/APC Connector
1480-1480nm				T= 12/130 PMDC Fiber	2= 2mm Cable	15= 1.5m	LC/PC= LC/PC Connector
1590-1590nm				R= 25/250 PMDC Fiber	3= 3mm Cable	20= 2.0m	SC/UPC= SC/UPC Connector