

## 808/920~980nm PM WDM Filter

### FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

### APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



### SPECIFICATIONS

Parameters	Unit	Standard	High Isolation
Pass Channel Wavelength Range $\lambda_1$	nm	808+/-10	
Reflective Channel Wavelength Range $\lambda_2$	nm	920+/-10, 930+/-10, 950+/-10, 980+/-10	
Insertion Loss over $\lambda_1$ @ Pass Channel	dB	$\leq 1.4$	$\leq 1.6$
Insertion Loss over $\lambda_2$ @ Reflective Channel	dB	$\leq 1.2$	
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation over $\lambda_1$ @ Reflective Channel	dB	$\geq 12$	
Isolation over $\lambda_2$ @ Pass Channel	dB	$\geq 25$	$\geq 45$
Optical Return Loss	dB	$\geq 50$	
Extinction Ratio	Standard	dB	$\geq 18$
	High ER Type	dB	$\geq 20$
Fiber Type	-	PM850 Fiber or PM980 Fiber PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Polarization Alignment	-	Slow Axis	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	$\phi 5.5 \times L 35$
	Metal Box	mm	$L 120 \times W 12 \times H 10$

**Note:** 1. Specifications are for device without connectors; Specifications may change without notice.

2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.

3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

4. High ER type can only work in slow axis at pass port.

### ORDERING INFORMATION (PN)

FPWM-NN	NN	- C	(C)	C	(C)	- (C)	C	C	NN	- CC/CCC
Ref Wavelength	Pass Wavelength	Ref. Fiber	Ref. Fiber2	Type	Isolation	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
92~920nm	81~808nm	P= Same Fiber	P= Same Fiber	H= High ER	L= High Iso	M= Metal Box	2=PM850Fiber	B= Bare Fiber	05=0.5m	N=Without Connector
93~930nm		S= Corr. SM Fiber	S= Corr. SM Fiber	Blank for	Blank for	Blank for SST	H=PM980Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
95~950nm			Blank for Y Type	Standard	Standard		E=PM1060L Fiber	2=2mm Cable	15=1.5m	LC/PC =LC/PC Connector
98~980nm							R=25/250 PMDC Fiber	3=3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector