

915/980nm High Power PM WDM

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks
- CATV Networks



SPECIFICATIONS

Parameters	Unit	Standard	High ER Type
Pass Channel Wavelength Range λ_1	nm	970~990	
Reflective Channel Wavelength Range λ_2	nm	910~920	
Insertion Loss over λ_1 @ Pass Channel	dB	≤1.2	≤1.4
Insertion Loss over λ_2 @ Reflective Channel	dB	≤1.0	
Configuration	Y Type	-	3-port
	X Type	-	4-port (2x2 WDM)
Isolation over λ_1 @ Reflective Channel	dB	≥12	
Isolation over λ_2 @ Pass Channel	dB	≥25	
Optical Return Loss	dB	≥50	
Extinction Ratio	dB	≥18	≥20
Fiber Type	-	PM850 Fiber or PM980 Fiber PM1060L Fiber (E) or PM1060L-FA Fiber (L) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Polarization Alignment	-	Slow Axis	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	W	1, 2, 3, 5, 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(\varnothing)5.5x35 (≤5W); (\varnothing)6.0x48 (5~10W)
	Metal Box	mm	(L)90x(W)12x(H)10 (>10W); (L)120x(W)12x(H)10 (≤10W)

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 5. High ER type can only work in slow axis at pass port.

ORDERING INFORMATION (PN)

FPWM-NN	NN	- C	(C)	C	-HP NN	-(C)	C	C	NN	-CC/CCC
Ref Wavelength	Pass Wavelength	Ref. Fiber	Ref. Fiber2	Type	Optical Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
91~915nm	98~980nm	P= Same Fiber S= Corr. SM Fiber	P= Same Fiber S= Corr. SM Fiber Blank for Y Type	H= High ER Standard	1= 1W 5=5W 10=10W 20=20W	M=Metal Box Blank for SST or >10W	2=PM850Fiber H=PM980Fiber E=PM1060L Fiber R=25/250 PMDC Fiber	B= Bare Fiber L= Loose Tube 2=2mm Cable 3=3mm Cable	05=0.5m 10=1.0m 15=1.5m 20=2.0m	N=Without Connector FC/APC=FC/APC Connector LC/PC =LC/PC Connector SC/UPC=SC/UPC Connector